


makes a difference



Pressure Washers 2015



Determination and Partnerships are the keys to success.

Achieving success requires three ingredients: self-confidence, good training and a clear goal. In today's fast-paced world, reaching your goal without help is difficult. More than ever, success depends on a strong partnership. You'll want to team with somebody whose capabilities you trust, whose equipment is manufactured to the highest quality standards and whose attention to detail and professionalism is top-notch. You'll want to partner with a company like Kärcher; working together, you will achieve your goals quickly and efficiently.






Table of contents

Hot Water, Electric Powered	Page	8	Cold Water, Gas Powered	Page	30
Hot Water, Gas Powered	Page	20	Trailer Systems	Page	32
Cold Water, Electric Powered	Page	22	Detergents	Page	34



Unbeatable versatility - high-pressure cleaning with Kärcher.

The name Kärcher is synonymous worldwide with power, quality, innovation and for cleaning expertise which has been setting the standard for over 75 years. Kärcher invented the high-pressure cleaner in 1950 and has been refining the principle of high-pressure cleaning ever since. More performance with less consumption, longer service life with shorter cleaning times. As a world market leader, Kärcher offers a range of products that leaves nothing to be desired in terms of technical refinement and versatility – operating with cold or hot water, powered by electric motors or internal combustion engines, mobile or stationary.

1 State-of-the-art burner technology

■ Hot water high-pressure cleaners from Kärcher undergo continuous development. Thanks to an optimized heat exchanger and new turbo fan, emissions can be reduced and fuel consumption lowered. This is environmentally-friendly and cost-effective.


2 Durable pump technology

Kärcher high-pressure cleaners are manufactured in our own plants by our own specialists. This guarantees superior "made by Kärcher" quality.

3 Save energy and protect the environment

■ Kärcher's new generation of hot water high-pressure cleaners are the first in the world to feature an ecolefficiency mode. Simply select the ecolefficiency mode (blue) to switch to the most efficient temperature (60 °C) with full water flow. The advantage: The burner cycles are optimised and the fuel consumption (as compared to full-load operation at 80 °C) is reduced by as much as 20%.





4 Advanced nozzle technology

All nozzles for all Kärcher high-pressure cleaners are designed for their specific use in order to achieve optimal results. For example, the power nozzle increases the impact pressure by 40%.

5 Heat-Transfer efficiency design

- With today's high fuel List Prices, you can benefit from cleaning faster and better with hot water while saving some serious money.
- Among these innovations: Heat is both absorbed and 'bounced' off a fire brick floor, retaining the heat longer in the heating chamber; A double-pass coil forces water to pass through the heating chamber twice for added heat-transfer efficiency; Outside air serves as an insulating blanket and is pre-heated prior to being injected into the flame for optimum combustion.


6 Unmatched mobility

■ Kärcher high-pressure cleaners are always raising the bar for mobility. HDS compact, medium-duty and super class models are in a jogger design: large rubber tire wheels at the rear and swivel castors at the front. The new HDS upright range introduces the tried and tested sack trolley principle of the cold water units to the realm of Kärcher hot water high-pressure cleaners. What they all have in common are ergonomic handles and perfect weight distribution for quick relocation, safely and with minimal effort. Transport is simplified by fork-lift compatibility, lashing eyelets and tilting aids.



Efficient pressure washer cleaning.

The name Kärcher is synonymous worldwide with power, quality, innovation and for cleaning expertise which has been setting the standard for over 75 years. Kärcher invented the high-pressure cleaner in 1950 and has been refining the principle of high-pressure cleaning ever since. More performance with less consumption, longer service life with shorter cleaning times. As a world market leader, Kärcher offers a range of products that leaves nothing to be desired in terms of technical refinement and versatility – operating with cold or hot water, powered by electric motors or internal combustion engines, mobile or stationary.











HD or HDS: the advantage at a glance.

HD: ideal for removing loose dirt and cleaning large areas

With cold water pressure washers, the temperature has no influence on the cleaning action. The impact pressure is mainly decisive for the cleaning result. For removing stubborn dirt such as oil and grease, good cleaning results can generally be achieved by using detergents. The advantages of HD are as follows: Less expensive, no water heating energy costs, low service and repair costs, fewer components and no heating coil.

HDS: ideal for removing stubborn dirt, antibacterial action and sensitive surface

Hot water pressure washers can increase the supplied water temperature from about 54°F to about 302°F. This allows a reduction of the working pressure, cleaning time and the amount of detergent to be used. Cleaning with hot water therefore offers numerous options for optimizing the cleaning process due to the advantages of HDS: Same cleaning effect at lower working pressure, improved cleaning results at identical working pressure, more effec-

tive dissolving of lubricant residues, shorter cleaning times and labor cost saving, efficitive antibacterial action, shorter drying time and gentle to sensitive surfaces.

Clear cost comparison

Cold water high-pressure washer
Total costs: 1 man/hour = \$25.88

Hot water high-pressure washer
Total costs: 1 man/hour = \$21.15

\$6.00

\$19.35

Running costs/man-hour

HD labour costs

Saving per man-hour (\$4.74 \(\) 18 %)

HDS labour costs (up to 40% time-saving when using a hot water pressure washer)

Calculation based on 100 man-hours/year.

Hot Water | Electric Powered | Diesel Heated



HDS upright class - mobility at its finest.

These high-performance, robust upright machines offer outstanding maneuverability, easy transport and intuitive operation. Ideal for tradesmen, commercial use and contract cleaners.



















1 Compact design

- Space-saving storage and transport.
- Spill-proof pump and fuel tank for transport lying down.
- Ideal for small service vehicles.

2 Fine-mesh water filter

- Efficiently protects high-pressure pump against contamination.
- $\hfill\blacksquare$ Easy to remove from outside.

3 Innovative upright design

- Effortless transport over landings or stairs.
- Large wheels for unpaved surfaces.



		HDS 1.7/12 U Ed
		 Industrial-grade axial pump Efficient burner uses less fuel Complete machine shut-down at the gun Low fuel shut-off / low water protection High temperature protection ETL certified to UL and CSA standards
Technical Data		
GPM		1.7
PSI		1200
HP		2.2
Electrical		120V / 1ph
Amps		15
Pump		Kärcher axial
Ship Weight	lbs.	150
Dimensions (L x W x H)	inch- es	24.3 x 24.3 x 39
Order No.		1.064-037.0

Hot Water | Electric Powered | Diesel Heated



Compact "C" Series

Kärcher's German-built electric hot water machines are the most advanced on the market, featuring Kärcher's patented axial pump integrated with a 2-pole motor for optimum efficiency. Kärcher's efficient and compact downdraft-fired burner uses far less fuel than standard coils. Units come standard with low-fuel shut-off, low-water protection, high-temperature shut-off, thermal overload protection, soft-grip gun, and 50' hose. All units are ETL certified to UL and CSA standards.





















1 Efficiency

- ecolefficiency mode economical and environmentally friendly, even during longer periods of use.
- Reduces fuel consumption and CO₂ emissions by 20%.
- Accurate cleaning agent dosing unit with clear rinse function.

2 Ease of use

- Intuitive operation with large single-button selector switch.
- $\hfill \blacksquare$ Easy fillable tanks for fuel and detergent.

3 Storage

- $\hfill \blacksquare$ Lockable accessory compartment for nozzles, tools, etc.
- Integrated power cord and spray lance holder.

4 Mobility

- New push bar handle for easier maneuverability and control.
- Robust wheels and steering mechanism for maneuverability.
- Large integrated handles in the chassis.
- Integrated tilting aid for effortlessly negotiating obstacles such as steps and curbs.



		HDS 2.3/12 C Ed	HDS 3.0/20 C Ea
		 Kärcher's direct-drive axial pumps Industrial-grade axial pump Efficient burner uses less fuel Complete machine shut-down at the gun Low fuel shut-off / low water protection High temperature protection ETL certified to UL and CSA standards 	
Technical Data			
GPM		2.3	1.3-3.0
PSI		1100	460-2000
НР		2.8	5.6
Electrical		110 -120V / 1ph	220-240V / 1ph
Amps		20	20
Pump		Kärcher axial	Kärcher axial
Ship Weight	lbs.	270	279
Dimensions (L x W x H)	inches	42 x 26 x 36	42 x 26 x 36
Equipment			
Variable flow and PSI			
Detergent tank		•	•
	/stem		
Steam stage			•
RM 110 scale inhibitor sy Steam stage Pivoting spray lance			
Steam stage			
Steam stage Pivoting spray lance		-	
Steam stage Pivoting spray lance Fixed spray lance		•	•

Options (field installed)								
Product name	Order No.	Description						
Servo Control	4.775-526.0	Servopress Controller, Less than 3.3 GPM						

Hot Water | Electric Powered | Diesel Heated



Full-size power

The perfect machines for car dealers, building trade, agriculture and municipal use: our super class machines set standards in terms of technology, performance, ease of use, economy, service life and environmental protection.

























1 eco!efficiency mode

■ Kärcher's Classic hot water pressure washers are the first in the industry to offer ecolefficiency mode. This enables the machine to operate in the most economical temperature range (140° F) and at the maximum water flow rate, reducing fuel consumption by 25% and optimizing burner operating cycles compared to full-load operation at 180° F.

2 Service switch

Kärcher's Classic series features a service switch that offers a choice of five settings to suit local water hardness. This allows optimum metered quantities of anti-scaler and corrosion inhibitor to be added to the water supply, and prevents the buildup of lime scale on the heater coil. Operating data can be called up any time, allowing you to make continual adjustments.

3 Time-proven burner technology with new turbo fan

■ Kärcher burner technology not only translates to more economical operation, but also makes our hot water pressure washers trendsetters in environmental protection thanks to their low emissions and highly efficient operation.

4 Easy Press and Servo Control (optional accessory)

■ The Easy Press trigger gun significantly reduces holding and operation effort, and the precise Servo Controller allows the user to adjust water flow rate and operating pressure directly from the trigger gun.



		HDS 4.0/20-4M Ea	S 4.0/20-4M Ea HDS 4.5/22-4M Ea		HDS 3.5/23-4M Eg	HDS 5.0/30-4S Eb	HDS 5.0/30-4S Ec
		·	kial pump ses less fuel shut-down at the gun low water protection protection temp, & soap he turn of a knob				
Technical Data	1						
GPM		2.0-4.0	2.4-4.5	2.0-3.5	2.0-3.5	2.4-5.0	2.4-5.0
PSI		460-2000	460-2250	460-3000	460-2300	460-3000	460-3000
HP		8	9.5	9.5	8.1	11	11
Electrical		220-240V / 1ph	220-240V / 1ph	220-240V / 1ph	200-208V / 1ph	230V / 3ph	460V / 3ph
Amps		30	30	30	30	30	15
Pump		Kärcher axial	Kärcher axial	Kärcher axial	Kärcher axial	Kärcher axial	Kärcher axial
Ship Weight	lbs.	396	443	405	105 368 423		413
Dimensions (L x W x H)	inches	52.5 x 29.5 x 41.5	52.5 x 29.5 x 41.5	52.5 x 29.5 x 41.5	52.5 x 29.5 41.5	52.5 x 29.5 x 41.5	52.5 x 29.5 x 41.5
Order No.		1.071-427.0	1.071-428.0	1.071-431.0	1.071-407.0	1.071-625.0	1.071-626.0
Color		•	•	•	•	•	•

Options (field installed)		
Product name	Order No.	Description
100' Pivot Hose Reel	8.750-685.0	100' Pivot Hose Reel, 3/8" x 100' with pin lock
Classic pivoting hose reel bracket mount	8.921-775.0	Classic pivoting hose reel bracket mount (*requires additional parts)
Coupler	8.709-531.0	Coupler, Twist Seal, 3/8" Socket, Female
Street Elbow	9.802-114.0	Street Elbow, 3/8" Mpt x 3/8" Fpt / 90 Degree
Servo Control	4.775-471.0	Servopress Controller, 3.3 to 4.9 GPM

Hot Water | Electric Powered | Electric Heated



*Shown with optional Servo Control.

HDS-E 3.3/25-4M Ec powerful, exhaust-free cleaning.

The emission-free HDS-E 3.3/25-4M Ec with electric heater is ideal where exhaust gases are undesirable or prohibited. Thanks to the unique type of heater insulation and Kärcher ecolefficiency mode, the HDS-E 3.3/25-4M Ec is efficient and eco-friendly. Models are ETL certified to UL & CSA safety standards.























- 1 High energy efficient, for high cost savings
- Improved highly effective boiler insulation saves up to 40% energy in standby mode.
- 2 High working temperature
- 15 gallon large hot water tank (max. 185 °F).
- Up to 136 °F in continuous operation at full load or 176 °F through servo control.

- 3 Environmentally friendly
- eco!efficiency mode for economical operation and ideal cleaning results.
- Less energy consumption saves the environment.
- 4 Designed with mobility in mind
- Robust, large rubber wheels with enhanced castor and brake.
- Tilting aid located on back of machine.
- Tie-downs point for safe transport and loading.



HDS-E 3.3/25-4M Ec

- No fossil fuel emissions or fumes
- Quiet, clean and user friendly
- \blacksquare 90°F temperature rise under full load; 130°F rise under partial load
- Infinitely variable water pressure, temperature control and soap metering

Technical Data		
GPM		3.3
PSI		2200
НР		7.5
Electrical		460V / 3ph
Amps		48
Pump		Kärcher axial
Ship Weight	lbs.	290
Dimensions (L x W x H)	inches	46 x 28 x 44

Equipment

Trigger gun		Easy Press
High-pressure hose	feet	33
Spray lance	inches	41
Power nozzle		
Dry running protection		
Servo Control		
Order No.		1.030-252.0

 \blacksquare Included in delivery.

Optional Accessories		
Product name	Order No.	Description
100' Pivot Hose Reel	8.750-685.0	100' Pivot Hose Reel, 3/8" x 100' with pin lock
Classic pivoting hose reel bracket mount	8.921-775.0	Classic pivoting hose reel bracket mount (*requires additional parts)
Hose	8.918-280.0	Hose, 3/8"x 6'
Caster wheel	6.435-777.0	Caster wheel, unlocked
Bolts	7.303-236.0	Bolts (requires 4)
Spacer sleeve	5.111-065.0	Spacer sleeve (requires 4)
Coupler	8.709-531.0	Coupler, Twist Seal, 3/8" Socket, Female
Street Elbow	9.802-114.0	Street Elbow, 3/8" Mpt x 3/8" Fpt / 90 Degree
Dirt blaster nozzle	9.302-444.0	Dirt blaster nozzle
Surface cleaner	2.640-355.0	Surface cleaner, FR 30 ME
Nozzle kit	2.639-187.0	Nozzle kit for FR
Coupler	4.403-002.0	Coupler
Servo Control	4.775-470.0	Servo Control

Hot Water | Electric Powered | Electric Heated



HDS 801E Series

This Classic Series unit is an electric powered machine that provides electrically-generated heat for those special applications where hot water is required but where gas or oil-fired ignition is prohibited. The 801E is optimal for use in hospitals, food factories, and other areas where indoor emissions present a concern. Models are ETL certified to UL & CSA safety standards.









Powerful and durable

- Robust, three-piston axial pump features detergent-resistant brass cylinder head and stainless steel valves; pump is protected by pressure switch, over flow valve and soft- dampening system
- Galvanized, powder-coated steel chassis and high-impact cover protect components from damage.
- Built-in, corrosion-proof detergent tank allows for application of soap while spraying under high pressure.
- Double thermal overload protection guards against damage from high amps and temperatures.
- Proprietary scale inhibiting system prevents build-up of mineral deposits inside the heating element
- Durable 41" insulated stainless steel wand rotates 360° under pressure.
- Air-cooled motor with overload protection for maximum safety and performance
- Power Nozzle delivers 40% more impact than standard nozzles for faster cleaning

Smart features

- Pressure-controlled auto start/stop ensures motor and pump shut down automatically when trigger gun is released.
- Infinitely variable water pressure, volume, temperature control and detergent metering.
- Easy-Press trigger gun features a shock absorbing soft-grip handle and ongun swivel connection.
- Electrically heated, stainless steel boiler features 24 KW integrated heating element and rapid pre-heating chamber.
- Delivers 90° F temperature rise under full load; 130° F rise under partial load
- The separate high-speed heating chamber and hot water tank ensure rapid availability of spray water. A mixer valve on the control panel mixes hot water with cold water from the float tank.
- Low-water protection switches off the heating element when incoming water supply is too low.



HDS 801E

- lacksquare No fossil fuel emissions or fumes
- Quiet, clean and user friendly
- 90°F temperature rise under full load; 130°F rise under partial load
- Infinitely variable water pressure, temperature control and soap metering

Technical Data		
GPM		3.3
PSI		2200
НР		7.5
Electrical		550V / 3ph
Amps		54
Pump		Kärcher axial
Ship Weight	lbs.	292
Dimensions (L x W x H)	inches	46 x 28 x 44
Order No.		1.030-701.0

Optional Accessories		
Product name	Order No.	Description
200' Kärcher Non-pivot Hose Reel	8.750-683.0	200' Kärcher non-pivot hose reel, hose not included
100' Kärcher Non-pivot Hose Reel	8.750-685.0	100' Kärcher non-pivot hose reel, hose not included
200' Kärcher Pivot Reel	8.750-684.0	200' Kärcher pivot reel, hose not included
Mounting kit	8.919-683.0	Mounting kit, non-pivot, 45-degree arm
Mounting kit	8.919-684.0	Mounting kit, non-pivot, vertical arm (includes mounting brackets, hardware and jumper hose)
Mounting kit	8.919-685.0	Mounting kit, pivot reel (includes mounting brackets, hardware and jumper hose)

Hot Water | Electric Powered | Natural Gas or LP-Heated



Classic NG or LP Cabinet

The innovative, rugged design of the new Kärcher Classic HDS natural gas and LP-heated cabinet pressure washer delivers up to 5 gpm at 3,000 psi of industrial power. Built in the U.S.A., each model is constructed with anodized structural rivets, a water cooled electric motor, standard auto/start/stop and Kärcher's axial direct-drive pump backed by a 7-year warranty. All models are ETL certified to UL and CSA safety standards.



















1 Easy to service and operate

- All-access cabinet design with six lift out panels and easy lock fasteners provides easy access to components for maintenance in tight situations.
- Swing-out cast iron burner ring with separate "stay-in-place" ignition pilot light allows easy access and removal of the burner ring.
- Standard electronic ignition eliminates the hassle of having to monitor and light pilot flame.

2 Fully configurable

- All models are readily designed to accept a full line of Easy-Add field installed option kits.
- Inlet/outlet connections can be easily moved to either side of the unit.

3 Designed to last

- The extra-durable heating coil is made of leak-free, cold-rolled, schedule 80 steel pipe and is wrapped with a thick foil blanket insulation that keeps cabinet walls cool to the touch.
- Pulsation damper reduces vibrations on the high pressure side of the system.
- Integrated RM 110 reservoir protects the machine from scale build-up in the heating coil.
- Water-cooled electric motor.

4 Easy press trigger gun

- Ergonomic design with soft grip for greater comfort.
- Power nozzle delivers 40% more cleaning power.
- 41" jet pipe lance that rotates under pressure.



Easy to operate controls with instant feedback lights



- 1 Hour meter
- 2 Power
- 3 RM110
- 4 Detergent valve
- 5 Burner motor switch
- 6 Motor on
- 7 Thermostat control
- 8 Pressure gauge

Technical Data and Equipment

Classic NG or LP Cabinets

- Kärcher's axial direct-drive pump with 7-year warranty
- Integrated RM 110 reservoir
- Built-in auto start/stop
- Steam stage
- Pulsation damper

- Kärcher Easy Press trigger gun
- Kärcher Power Nozzle
- "Stay-in-Place" ignition pilot light with swing out burner ring
- Cool wall cabinet construction

Natural gas-heated

Order No.	Model	GPM	PSI	Volt- age	Phase	Amps	НР	Pump	Pump/ Motor RPM	вти	Dimensions (L x W x H) inches Unit / Shipping	Weight (lbs.) Unit / Shipping
1.109- 722.0	HDS 4.5/22 Ea ST NG	4.5	2200	230V	1 ph	30	9.5	axial	1725	393,000	49 x 24 x 48 57 x 24 x 48	695 / 865
1.109- 729.0	HDS 3.5/30 Ea ST NG	3.5	3000	230V	1 ph	27	9.5	axial	1725	310,000	49 x 24 x 48 57 x 40 x 64	695 / 865
1.109- 742.0	HDS 5.0/30 Eb ST NG	5	3000	230V	3 ph	27	11	axial	1725	398,000	49 x 24 x 48 57 x 40 x 64	700 / 870
1.109- 743.0	HDS 5.0/30 Ec St NG	5	3000	460V	3 ph	19	11	axial	1725	398,000	49 x 24 x 48 57 x 40 x 64	700 / 870

LP gas-heated

1.109- 763.0	HDS 4.5/22 Ea ST LP	4.5	2200	230V	1 ph	30	9.5	axial	1725	393,000	49 x 24 x 48 57 x 40 x 64	695 / 865
1.109- 770.0	HDS 3.5/30 Ea ST LP	3.5	3000	230V	1 ph	27	9.5	axial	1725	310,000	49 x 24 x 48 57 x 40 x 64	695 / 865
1.109- 783.0	HDS 5.0/30 Eb ST LP	5	3000	230V	3 ph	27	11	axial	1725	398,000	49 x 24 x 48 57 x 40 x 64	700 / 870
1.109- 784.0	HDS 5.0/30 Ec St LP	5	3000	460V	3 ph	19	11	axial	1725	398,000	49 x 24 x 48 57 x 40 x 64	700 / 870

Simple to configure with "Easy-Add" option kits

Order No.	Description
2.744-008.0	Remote Kit single station
6.685-195.0	Chemical solenoid valve (brass) for use with remote kit
8.708-846.0	Chemical solenoid valve (stainless steel) for use with remote kit
9.801-040.0	Draft diverter, 10"
8.753-474.0	Damper, draft 10"

Hot Water | Gas Powered | Diesel Heated



Classic HDS Pe Cage

These durable, skid-mounted models are designed for optimum cleaning performance at remote locations and feature Kärcher's unique 12V downdraft burner system. The highly compact burner is more than 92% efficient, resulting in better heat transfer using much less fuel. They feature belt-drive crankcase-style pumps. Certified to UL and CSA safety standards.









Powerful and durable

- Industrial-duty, tri-plunger, oil-bath, belt-drive K\u00e4rcher KT pump with 7-year warranty, brass pump head, and Tru-Trak belt adjustments; operates at a low RPM for low-maintenance operation and long life.
- Heavy-gauge 11/4" steel frame with powder coat finish for all-weather protection; with vibration isolators and forklift guides.
- Reliable gas-powered engines with electric start.
- Proprietary scale inhibiting system prevents build-up of mineral deposits inside the coil.
- Rust-free 11 gal. Polyethylene diesel and gasoline tanks for hours of uninterrupted operation.
- Warning lights monitor fuel and scale inhibitor levels; low-fuel shut-off protects fuel pump.

Smart features

- Kärcher's 92% efficient top-fired burner delivers more heat from less fuel for the lowest operating costs in the industry.
- Detergent metering valve allows for infinitely variable application of soap while washing in high-pressure mode.
- 50' K\u00e4rcher high-pressure steam hose rated for 311\u00df F connects to the gun with an integrated swivel connection.
- Infinitely variable operating pressure, water volume, temperature control, and detergent metering.
- Unsurpassed K\u00e4rcher safety features include pressure switches, rupture disk, low-water and low-fuel protection that shuts down burner when incoming water and fuel are insufficient or interrupted.
- Ergonomically designed soft-grip Easy Press trigger gun minimizes operator fatigue.



		HDS 4.0/32 Pe Cage	HDS 5.0/32 PE Cage	HDS 5.5/35 Pe Cage
		 Rugged frame construction Reliable belt-drive crankcase pumps Compact and highly-efficient burner Low-fuel cut off Anti-scale system Electric start engines 		
Technical Data				
GPM		4.0	5.0	5.5
PSI		3200	3200	3500
Engine		Honda GX390	Vanguard 16	Honda GX630
СС		389	479	688
Drive		Belt	Belt	Belt
Pump		Kärcher KT	Kärcher KT	Kärcher KT
Ship Weight	lbs.	692	762	741
Dimensions (L x W x H)	inches	51 x 33 x 43	51 x 33 x 43	51 x 33 x 43
Order No.		1.575-615.0	1.575-616.0	1.575-617.0

Cold Water | Electric Powered



The compact class – fast and thorough.

These reliable, compact all-rounders offer the benefits of low weight, compact dimensions, easy handling and high cleaning performance. Ideal for workshops, courtyards, etc.





















1 EASY Press hand spray gun

- Ergonomic design for ease of use.
- EASY press trigger for fatigueless use.
- With soft grip for greater comfort.

2 Telescopic push handle

- Large aluminium profiles provide stability and good manoeuvrability.
- Holds accessories in the extended position.
- Retracts for convenient, space-saving transport, such as in service vehicles or compact cars.

3 Outstanding mobility

- lacksquare For rapid cleaning at different locations.
- Space-saving storage in service vehicles.
- Fast set-up thanks to integrated storage options.

4 Automatic pressure cut-off

- Switches off immediately when work is interrupted.
- For reduced energy and water consumption.









HD 1.8/13 C Ed

HD 2.3/15 C Ed*

HD 3.0/20 C Ea

- $\hfill\blacksquare$ No fossil fuel emissions or fumes
- Ergonomic design
- Low-pressure soap injection system
- Complete trigger shut off
- Triple changeover nozzle
- ETL certified to UL and CSA standards

Technical Data			
GPM	1.8	1.0-2.3	1.1-3.0
PSI	1300	435	300-2000
HP	2.2	3.2	5.2
Electrical	120V / 1ph	120V / 1ph	240V / 1ph
Amps	15	20	20
Pump	Kärcher axial	Kärcher axial	Kärcher axial
Trigger Gun	Extended Trigger Gun	Easy Press	Easy Press
Variable Flow		•	•
Ship Weight lbs.	63	68	68
Dimensions (L x W x H) inches	15 x 14 x 37	15 x 14 x 37	15 x 14 x 37
Order No.	1.514-136.0	1.150-626.0	1.150-625.0

^{*} Servo Control not an option

Cold Water | Electric Powered



Medium class - excellent features.

These medium class machines are extremely mobile and user-friendly with low-speed four-pole single or three-phase motors for continuous use.





















1 CHEM switch

- Unique CHEM switch system allows operator to switch between two on-board detergent tanks without interruption; includes precise two-way metering valve to accurately vary detergent volume.
- Easy cleaning agent bottle changeover.

2 Smart features

- Rear cable/hose rack provides added convenience.
- Kink-free, 33-ft. high-pressure hose is easy to wind, with integrated connection inside the gun which swivels under full pressure.
- Integrated lance holder for easy transport.
- Parking position for short breaks.

3 Powerful and durable

- Robust, three-piston axial pumps features detergent-resistant brass cylinder head and stainless valves; pumps is protected by pressure switch and over flow valve.
- Built-in motor protection against voltage fluctuations and excessive temperatures
- Single-phase unit features ground-fault circuit interrupter (GFCI) for operator safety
- Low-speed, 4-pole, air-cooled motor runs quieter and cooler than conventional motors thus prolonging its service life
- Ceramic-coated piston.

4 Outstanding mobility

- Large wheels for uneven surfaces.
- Upright design for easy, ergonomic transport.
- Integrated tilting aid at the rear.



HD 3.0/20-4M Ea*

- No fossil fuel emissions or fumes
- Ergonomic design
- Low-pressure soap injection system
- Complete trigger shut off
- Triple changeover nozzle
- Comes with variable flow ServoPress gun
- ETL certified to UL and CSA standards

Technical Data		
GPM		1.3-3.0
PSI		435-2000
НР		4.7
Electrical		220-240V / 1ph
Amps		20
Pump		Kärcher axial
Ship Weight	lbs.	105
Dimensions (L x W x H)	inches	18 x 16 x 40
Order No.		1.524-126.0

Cold Water | Electric Powered



Super class – perfect for tough jobs in non-stop use.

Where vast amounts of dirt accumulate every day, reliable Kärcher super class models provide indispensable services. Ideal for use in the construction, agricultural and forestry sectors as well as industry and municipal facilities.



















1 Powerful and durable

- Robust, three-piston axial pumps features detergent-resistant brass cylinder head and stainless valves; pumps is protected by pressure switch and over flow valve.
- Built-in motor protection against voltage fluctuations and excessive temperatures
- Single-phase unit features ground-fault circuit interrupter (GFCI) for operator safety
- Low-speed, 4-pole, water-cooled motor runs quieter and cooler than conventional motors thus prolonging its service life
- Ceramic-coated piston.

2 Smart features

- Rear cable/hose rack provides added convenience.
- Kink-free, 33-ft. high-pressure hose is easy to wind, with integrated connection inside the gun which swivels under full pressure.
- Integrated lance holder for easy transport.
- Parking position for short breaks.

3 Outstanding mobility

- Large wheels for uneven surfaces.
- Upright design for easy, ergonomic transport.
- Integrated tilting aid at the rear.





- No fossil fuel emissions or fumes
- Ergonomic design
- Low-pressure soap injection system
- Complete trigger shut off
- Triple changeover nozzle
- Comes with variable flow ServoPress gun
- ETL certified to UL and CSA standards

Technical Data					
GPM		1.8-3.5	1.8-3.7	2.2-4.5	2.2-4.5
PSI		435-3000	435-2200	435-3200	435-3200
НР		9	6.9	10	10
Electrical		220-240V / 1ph	200-208V / 1ph	230V / 3ph	460V / 3ph
Amps		30	30	30	16
Pump		Kärcher axial	Kärcher axial	Kärcher axial	Kärcher axial
Ship Weight	lbs.	168	158	182	182
Dimensions (L x W x H)	inches	22 x 20 x 43	22 x 20 x 43	22 x 20 x 43	22 x 20 x 43
Order No.		1.286-127.0	1.286-115.0	1.286-128.0	1.286-129.0

Cold Water | Electric Powered



Compact food class – for strict hygiene requirements.

Cold water high-pressure cleaner for all-purpose industrial use in the sanitary/food industry. This top-of-the-range machine from the compact class allows you to regulate pressure and water quantity seamlessly.





















- 1 Convenient Easy Press
- Ergonomic design for convenient operation.
- Reduced exhaust and retention force for effortless operation.
- Soft grp surface for a secure grip.
- 2 High standard of hygiene
- Food-safe, non-marking high-pressure hose.
- Wear-resistant and non-marking grey wheels.
- Accepts inlet water at temperatures up to 180°F.

- 3 Practical detergent system
- Cleaning agent intake system for removing stubborn dirt.
- The "Inno Foam Set" high-pressure foam system can be used.
- 4 Variable pressure and water flow regulation
- lacksquare Directly on the machine.
- Gentle cleaning of sensitive surfaces.



HD 2.3/14 C Ed Food

- No fossil fuel emissions or fumes
- Ergonomic design
- Low-pressure soap injection system
- Complete trigger shut off
- Triple changeover nozzle
- ETL certified to UL and CSA standards

Technical Data		
GPM		2.3
PSI		1400
НР		3.2
Electrical		120V / 1ph
Amps		20
Pump		Kärcher axial
Ship Weight	lbs.	68
Dimensions (L x W x H)	inches	15 x 14 x 37
Order No.		1.150-629.0

Cold Water | Gas Powered | Direct Drive



HD Handtruck Design

This series of commercial-duty, gas-powered cold water pressure washers offers the ideal balance between professional performance and value. Powered by reliable Honda engines, all four models have Kärcher's German-engineered, direct-drive axial pump, rugged steel frame with handtruck design, tubed pneumatic tires and 50' of commercial-duty hose.







Powerful and durable

- Rugged steel frame and power platform, with easy-to-maneuver handtruck design, is painted with a black, wrinkle-coat finish for all-weather protection.
- Reliable Honda engine with two-year warranty, low-oil alert and silent-tone muffler; 9 and 13 HP models have an EZ-start valve for resistance-free pull starting of engine.
- Three-piston, direct-drive K\u00e4rcher axial pump with unique swash plate design has fewer moving parts for a highly efficient, smooth and quiet operation; brass cylinder head ensures extra durability and extended life.
- 50' durable wire braid hose
- Inlet strainer protects pump from debris in the water source.
- Top-mounted 100' hose reel (comes standard only on machines more than 3,000 PSI).

Smart features

- Easy-to-attach downstream detergent injector with brass soap nozzle.
- Four conveniently mounted, quick-couple spray nozzles for varying fan spray.
- Insulated, high-pressure trigger gun for hours of fatigue-free cleaning.

Outstanding mobility

- 10" tubed pneumatic tires for easy maneuvering on all terrains and to absorb vibration; front-mounted rubber feet also absorb vibration and keep the unit from "walking" during operation.
- $\hfill \blacksquare$ Upright design for easy, ergonomic transport.



		HD 2.5/24 P	HD 2.6/26 P	HD 3.1/31 P	HD 4.0/36 P
		 Reliable Honda engines Kärcher axial pump Reinforced upright steel fran Unmatched value 	ne	■ includes 100' hose reel	■ includes 100' hose reel
Technical Data					
GPM		2.5	2.6	3.1	4.0
PSI		2400	2600	3100	3600
Engine		Honda GC160	Honda GC190	Honda GX270	Honda GX390
сс		160	187	270	389
Pump		axial	axial	axial	axial
Ship Weight	lbs.	148	155	166	180
Dimensions (L x W x H)	inches	35 x 21 x 24	35 x 21 x 24	24 x 32 x 43	24 x 32 x 43
Order No.		1.575-105.0	1.575-106.0	1.575-107.0	1.575-108.0

Options (field installed)		
Product name	Order No.	Description
100' Non-pivot Hose Reel	9.801-253.0	100' non-pivot hose reel, hose not included

Trailer Systems | Customized Mobile Packages TRK-2500

Kärcher's TRK-2500 pressure washer trailer is designed to accommodate a variety of pressure washer skids. This trailer package is rugged, affordable, versatile, and easy to ship and store.

The TRK-2500 is made of rugged 10-gauge steel. The wheel and axle assembly features leaf-spring suspension of up to 3,500 lbs. The 39-inch tongue features a swing-away hinge that saves on storage space.

Customizing your trailer package is easy:

- Step 1: Select a compatible Kärcher pressure washer from page 18.
- Step 2: Customize your trailer with a broad selection of options and accessories, such as hose reels, electric or hydraulic brakes, etc.





- 1 Easy storage and shipping
- Swing-away hinge makes for easy storing and shipping.

- 2 Convenience Options
- Hose reel, utility rack and saddle box options available.



Options

TRK-2500

- Includes electric start engine and battery
- Electrical wiring recessed within tubular frame;
- lacktriangle Lighted license plate holder and recessed tail lights;
- 1,000 lb. swivel jack with a 2-inch ball coupler for quick and easy hook up of the trailer;
- 3-way ball valve for easy switching of the water flow from the holding tank to a faucet;
- High-density, polyethylene 200-gallon water tank with a 12-inch access port, 1 1/2-inch drain valve,

3/4-inch float valve and a 50-mesh inlet filter; and two 5/16-inch chains for additional safety.

Technical Data		
Axle		Single
Gross Vehicle Weight Rating (GVWR)	lbs.	3500
Water Tank	gallons	200
Ship Weight	lbs	1072
Order No.		1.103-819.0

Product name	Order No.	Description
Classic Series Skid Mounting Kit	8.917-296.0	Classic Series Skid Mounting Kit (Required for mounting pressure washer to trailer)
Options (field installed)		
Saddle Box	8.917-558.0	Saddle Box (each)
Rock Guard	8.917-559.0	Rock Guard
Utility Rack	8.917-560.0	Utility Rack
Options (factory installed)		
Electric Brakes	8.917-397.0	Electric Brakes
Electric Brake Breakaway Kit	8.917-553.0	Electric Brake Breakaway Kit
Hydraulic Brakes	8.917-398.0	Hydraulic Brakes
High Pressure Hose Reel	8.917-554.0	High Pressure Hose Reel
Low-Pressure Hose Reel	8.917-555.0	Low-Pressure Hose Reel
Rock Guard	8.917-557.0	Rock Guard

Detergents



Cleaning detergents for pressure washers.

Kärcher's cleaning detergents for pressure washers can optimize cleaning results while reducing cleaning time. Whether they lower energy consumption or reduce drain water pollution, they are ideal for use in industry, trade and food processing.

	Product description	Application	Primary mixture	Properties	Order No.	Container	Ship weight lbs
General cleaners							
	KD-100 All-Purpose Cleaner is a non-caustic,				9.803-789.0	5 gal pail	47
	butyl-based blend of ingredients formulated to				9.803-791.0	55 gal drum 1)	495
And the second s	provide a low-foaming detergent for safe removal of dirt and grime off a broad range of surfaces around the home or shop. It is formulated to pass through a pressure washer without damaging the high-pressure pump. Furthermore, it is safe to use on aluminum, stainless steel, glass, plastic, paint and fine automotive finishes.	General Purpose	130:1	Biodegradable			
	KD-120 All-Purpose Cleaner is a high-powered,				9.803-712.0	5 gal pail 1)	46
	non-caustic, general purpose cleaner with a bleach additive for extra-effective cleaning of floors, walls, cabinets, ceilings, pens and crates in a variety of applications, particularly kitchens, food processing and animal control. The chlorinated formula of KD-120 attacks stains, dirt, soils with carbon, oils, fats and greases plus removes mildew, mold, soap scum and tough odors. It's safe on aluminum, stainless steel, glass, plastic and paint. NSF registered for use in Federally inspected food plants.	Kitchens	60:1	Biodegradable			
5	KD-130 General Purpose Cleaner is effective on	<u> </u>			8.698-086.0	1 gal 1)	
	grease and grime while safe for most surfaces including plastic, aluminum, glass, chrome and painted surfaces. Makes 45 gallons of cleaning solution.	General Purpose	1:2	Biodegradable			
5					8.698-087.0	1 gal 1)	
	KD-110 House and Deck Wash is a safe and effective outdoor house, siding and deck wash. Won't harm most vegetation when used correctly. Makes 45 gallons of cleaning solution.	House and Deck	1:2	Biodegradable			
ehicle cleaners			,				
	VO 200 F. to Charath Makida Glassos				9.803-720.0	5 gal pail ³⁾	45
	KD-200 Extra-Strength Vehicle Cleaner is con- centrated, non-butyl, heavy duty vehicle wash				9.803-750.0	55 gal drum ²⁾	496
G	formulated to quickly and effectively remove dirt,				9.800-802.0	5/55 labels	
A Propose Course	grime, grease and road film from vehicles. It is distinguished by a special alcohol ingredient that	Vehicles		120:1	9.803-721.0	Mix kit, 1-pack	
201910	helps restore old vehicle painted surfaces and can even give paint a "newly waxed" appearance. KD- 200 is ideal for vehicle wash facilities where it can	verificies		120.1			

be used on tractor-trailers, heavy equipment, shop floors, metal or plastic tanks, RVs, trucks, and autos.



Vehicle cleaners	Product description	Application	Primary mixture	Properties	Order No.	Container	Ship weight lbs.
k t e a a f	KD-240 Super-Strength Vehicle Cleaner is a low-al-kaline, butyl-based degreaser detergent designed for the toughest of vehicle cleaning tasks. This special emulsifying formula contains high-powered cleaning agents for attacking grease, baked-on grime, road film and smoke trails. It is excellent as a pre-spray for cleaning engines, whitewall tires and vinyl and metal tops. KD-240 is biodegradable and contains Kärcher's exclusive pump and coil protection formula.	Vehicles	150:1		9.803-724.0	5 gal pail ³⁾	47
					9.803-754.0	55 gal drum ²⁾	506
9	KD-260 Heavy-Duty Vehicle Cleaner with wax is a highly concentrated vehicle cleaner that produces rich suds to increase dwell time and deep clean any vehicle surface. This formula is highly effective in	Vehicles	150:1	Biodegradable	9.803-726.0	5 gal pail ³⁾	48
					9.803-758.0	55 gal drum ²⁾	517
	removing road film and grime, yet is safe enough for use on polished aluminum. The wax additive gives				9.800-805.0	5/55 labels	
	KD-260 the extra performance feature that produces an attractive finish and shine for your vehicle. It also helps prevent dirt from adhering to the surface and reduces water spotting.				9.846-052.0	Mix kit**	
	KD-210 Vehicle Wash cleans cars, trucks, RVs, trailers, boats and rigs. Penetrates and loosens soil for effective and safe removal with a pressure washer. Makes 75 gallons of cleaning solution. NSF registered for use in Federally inspected food	Vehicles	1:4	Biodegradable	8.698-089.0	1 gal ¹⁾	46
Degreasers	kD-300 General Purpose Liquid Cleaner-Degreaser is a highly concentrated, non-caustic degreaser ideal for cleaning and removing oil and grease from vehicles and equipment in many applications. Based on its foaming properties, KD-300 works great with cold water pressure washers. Its non-caustic properties make it safe on fine automotive finishes and is especially effective in removing hard-to-clean hydrocarbon-based deposits, such as baked-on carbon, caked-on axle grease and even asphalt or tar.	Degreaser	150:1		9.803-730.0	5 gal pail ³⁾	47
	KD-320 Heavy-Duty Cleaner-Degreaser is a heavy-duty, non-butyl, non-caustic degreaser	Degreaser	150:1		9.803-732.0	5 gal pail ³⁾	48
	that quickly penetrates and removes grime, oil and grease in a variety of applications, including vehicles, equipment, RVs, drilling rigs, trucks and other structures. This high-concentrated blend is formulated to wet, penetrate and suspend soil, oils and grease and yet is safe to use indoors or outdoors on virtually every surface, including aluminum, stainless steel, glass, plastic, paint and fine automotive finishes.				9.803-772.0	55 gal drum ²⁾	505
	KD-330 Brown Soap Cleaner-Degreaser is an extra-strong, caustic-based cleaner and degreaser. It is ideal for cleaning heavy equipment, over-the-road vehicles and off-road machinery. This non-butyl detergent has just enough caustic to provide excellent cleaning horsepower while displaying the properties and usability of a non-caustic detergent. It is especially effective cleaning exhaust stains, road grime and heavy deposits of dirt ,and oil.	Degreaser	50:1	Biodegradable	8.916-134.0	5 gal pail ³⁾	42
					8.916-140.0	55 gal drum ²⁾	515
					8.916-133.0	5/55 labels	
					9.846-048.0	Mix kit, 9-pack 2)	
					9.846-047.0	Mix kit, 1-pack 3)	
	KD-340 Extra Heavy-Duty Cleaner-Degreaser is an highly concentrated, butyl-based degreaser designed for the toughest of vehicle cleaning tasks. The high-caustic formula has proven to be extra-effective in cleaning heavy equipment and off-road vehicles. It has the cleaning horsepower to remove heavy deposits of oil, grease as well as fifth wheel grease, hydraulic oils and diesel smoke stains.	Degreaser	128:1	Biodegradable	9.803-734.0	5 gal pail**	48
					9.803-739.0	55 gal drum*	515
Mineral Services					9.800-808.0	5/55 labels	
S. Table			9.84	9.846-056.0	Mix kit, 9-pack ²⁾		
					9.846-055.0	Mix kit, 1-pack ³⁾	

	Product description	Application	Pri- mary mixture	Properties	Order No.	Container	Ship weight It
egreasers	KD-360 Super-Duty Cleaner-Degreaser is an highly concentrated and caustic, non-toxic degreaser	Degreaser	1:4	Biodegradable	9.803-736.0	5 gal pail ³⁾	58
	that will tackle the toughest of cleaning tasks. It is extremely effective in removing the most difficult-to-clean oil, grease and hydrocarbon-based depositis. It cuts grease, grime, oil, burnt carbon and exhaust trails quickly and can even be used on everything from vent joods and ovens to engine blocks, heavy equipment and concrete floors. Do not use on aluminum, magnesium, galvanized metal				9.803-779.0	55 gal drum ³	632
<u></u>	or fine painted surfaces. KD-310 Equipment & Concrete Cleaner quickly and efficiently removes heavy grease from equipment and machinery as well as concrete surfaces.	Degreaser	1:4	Biodegradable	8.698-090.0	1 gal 1)	
	Concentrated formula makes 75 gallons of cleaning solution.						
ecialty cleaners	RM 110 RTU (Ready to Use) is a multi-component	Scale Inhibitor			9.556-111.0	4 x 1-gal	37
	product made from heat-resistant organic and in- organic salts. Its stabilizing action on the minerals,				8.698-058.0	12 x 1-quart	30
	which cause hardness in water, is based on its capacity to impede the growth of mineral deposits thus extending both the life of a heating coil and the time between acid cleanings. For units with output of 2.1-3.5 GPM Set pulse generator at 32-55 seconds. For units with output of 3.5-5.3 GPM Set pulse generator at 10-50 seconds.	n cause hardness in water, is based on its city to impede the growth of mineral deposits extending both the life of a heating coil and me between acid cleanings. For units with ut of 2.1-3.5 GPM Set pulse generator at 32-55 ands. For units with output of 3.5-5.3 GPM Set			9.556-011.0	5 gal pail	46
	RM 99 Solar Cleaner is specially formulated for cleaning solar and photovoltaic systems, and it's perfectly adapted to their unique surfaces. It is highly efficient, gentle on materials, biodegradable and removes even stubborn and greasy stains. It prevents the formation of limescale and maximizes the effectiveness of the system at minimum cost.	Solar cleaner	150:1	Biodegradable	8.698-094.0	5 gal (18.9 L)	
Į.	KD-110 Paint Prep provides a clean, paint-ready surface for professional results. Low foaming concentrate makes 180 gallons of cleaning solution.	Cleaner		Biodegradable	8.698-088.0	1.5 lb. ¹⁾	
uminum brightr	ner & coil cleaners						
	KD-460 Super-Strength Aluminum Brightner is an extrastrength, acid-based, aluminum brightener designed to tackle the toughest cleaning of truck trailers, aluminum wheels and for preparing aluminum for painting. Do NOT use on glass, polished aluminum or anodized aluminum. It uses	Brightner	5:1- 20:1	Biodegradable	9.803-746.0 9.803-747.0	5 gal pail ²⁾ 55 gal drum ²⁾	50
STILL	ammonium bifluoride, not hydrofluoric acid, and is non-fuming, yet effective in removing grease, oils, baked-on carbon and diesel smoke.						
	KD-480 Polished Aluminum Cleaner is a concen- trated, nonetching detergent formulated to quickly	Cleaner	Undi- luted	Biodegradable	9.803-748.0	5 gal pail ³⁾	48
	penetrate and remove grease, grime, dirt, road film and welding smut from polished aluminum and stainless steel surfaces. This ready-to-use, precise blend of acids, inhibitors and surfactants is bio- degradable and is a medium-foaming product that should be applied without dilution.		.5.00		9.803-749.0	55 gal drum ³ 632 1 gal ¹ 4 x 1-gal 37 12 x 1-quart 30 5 gal pail 46 1.5 lb. ¹ 5 gal pail ² 50 55 gal drum ² 537 5 gal pail ³ 48 55 gal drum ¹ 521	521
	KD-420 Acid-Based Coil Cleaner is a powerful,	Coil cleaner	16:1	Biodegradable	9.803-742.0	12 x 2 lbs.*	28
	acid-based coil cleaner that effectively attacks rust and hard water deposits in pressure washer hot water coils. KD-420 does not contain mineral acids, such as hydrochloric (muriatic), sulfuric and hydrofluoric acids that are commonly used in other coil conditioners. Even though it is acid-based, KD-420 is formulated so it can safely pass through a pressure washer without damaging the high-pressure pump. Do NOT use on aluminum or tin.				** UPS ground	limited qty.	



Graffiti remover



Easy-to-apply liquid formulas.

Kärcher Graffiti Remover products are easy-to-apply liquid formulas with deep penetrating action designed for use on many surfaces. There are three strong, fast-acting product formulations that safely penetrate and loosen the graffiti making it easy to remove. No extended soak time is needed and Kärcher Graffiti Remover can be applied and re-applied to wet surfaces without waiting to dry first, as is the case with other graffiti removers.

Graffiti removers	Product description	Application	Primary mixture	Properties	Order No.	Container	Ship weight lbs.
a control of the cont	Brick, Masonry & Concrete Cleaner re-liquefies and dissolves spray paint and marker tracks within seconds. No extended soak time is needed and	Brick Masonry Concrete	1:4	Biodegradable	8.698-039.0	Case of 4 x 1-gal jugs ²⁾	
	it can be re-applied to wet surfaces as needed, without waiting for the surface to dry.				8.698-040.0	Case of 12 x 1-	qt. bottles ²⁾
	Removes graffiti in 90 seconds or less.						
Pump guard							
	Kärcher Pump Guard provides freeze protection down to -25°F. Kärcher's environmentally friendly	Pump guard			9.558-998.0	16 oz.	1



Kärcher Pump Guard provides freeze protection down to -25°F. Kärcher's environmentally friendly Pump Guard is specifically formulated to prolong the life of your pressure washer. This specially formulated solution will protect your pressure washer from corrosion, premature wear and freezing (down to -25° F). It also adds lubrication to your pressure washer's valves and seals to prevent sticking in the future and provides superior protection over using anti-freeze alone.

Notes





makes a difference

Please contact us for more information:

Kärcher North America

750 W. Hampden Avenue, Suite 400 Englewood, CO 80110 U.S.A.

Tel. 800-456-6649 Fax 303-738-2818

www.karcher.com/us

Kärcher Canada

6535 Millcreek Drive Unit 67 Mississauga, ON L5N 2M2 Canada

Tel. 905-672-8233 Fax 905-672-3155

www.karcher.ca